



Certificate number: 2103741

Date issued 24th March 2021

Date expired 23rd March 2026 Original/Amendment Original

Kiwa UK Regulation 4 (KUKreg4) Approval

ATS3 – Without Production Surveillance

Issued by Kiwa Watertec (UK)

Evaluation Guideline: Kiwa UK – EG004
Reference Standards: Regulators Specification
Model Designations: see Appendix

Manufacturer: Crane BS&U (Viking Johnson).

Kiwa Watertec declares that legitimate confidence exists in the products specified in this certificate and supplied by the above organisation be relied on to comply with the above Evaluation Guideline and Standards, and can be marked with the KUKreg4mark.

The intended use of this certificate is for compliance with Regulation 4(1)a of the Water Supply (Water Fittings) Regulations 1999 England & Wales; 2009 Northern Ireland and 2014 Byelaws Scotland

This certificate has been issued in accordance with the Kiwa regulations for product certification

Signed on behalf of Kiwa Watertec

David Jay,
Business Unit Manager – Authorised Signatory
Kiwa Watertec

CERTIFICATE

3901770301

Kiwa Watertec
(A Trading Division of Kiwa Ltd)
26A Rassau Industrial Estate
Ebbw Vale
Gwent
NP23 5SD
United Kingdom
T +44 (0)1495 308185
uk.water@kiwa.com
www.kiwa.co.uk

Certificate issued to:
Crane BS&U – (Viking Johnson)
46 – 48 Wilbury Way
Hitchin
Herefordshire
SG4 0UD



UK Approval Certificate (page 2 of 2)

Appendix to Certificate 2103741

The following products are covered by this certificate -

<p>PRODUCT DESCRIPTION "UltraGrip" range of couplings, reducing couplings and end caps, with ductile iron and steel bodies with a black thermoplastic polymer (Rilsan Nylon T) coating and EPDM seals. For use with Steel, Ductile Iron, grey cast iron , PE (SDR11) and PVC pipes. and PVC pipes above and below ground use. ATS3 – Without Production Surveillance.</p>
<p>MODEL(S) UltraGrip range of Couplings and flange adaptors – DN40 to DN600. UltraGrip range of Reducing Couplings – DN32 to DN600. UltraGrip End Caps – DN40 to DN300.</p>
<p>SIZE: See model.</p>
<p>SCOPE: Manufacturer recommended maximum working pressure 10 Bar for sizes DN40 to DN300 and 16 Bar for sizes DN350 to DN600 & maximum operating temperature 23°C. Hygienic Purposes: Non-metallic materials suitable for continuous use up to 23°C. Above and below ground use.</p>
<p>MATERIALS Non-metallic materials assessed (BS6920) to point of discharge.</p>
<p>BACKFLOW PROTECTION NOTES N/A.</p>
<p>MARKING Viking Johnson, logo, pressure, model, range and other technical information.</p>
<p>ADDITIONAL NOTES All water contact & exposed components satisfy opacity requirements.</p>

Extra Notes